

The YAth Iranian Conference on Optics and Photonics (ICOP Y·YY), and the YEth Iranian Conference on Photonics Engineering and Technology (ICPET Y·YY).

> Shahid Chamran University of Ahvaz, Khuzestan, Iran, Feb. \-\(^\*, \forall^\*\)



# سنتز نانوذرات ۲iO با روش سل−ژل برای ساخت سلولهای خورشیدی حساس شده با رنگدانه طبیعی میوه جمبو

ماندانا شادکام ۱، تهمینه جلالی ۱، محسن محرابی و شهریار عصفوری ۲

اگروه فیزیک دانشگاه خلیج فارس، بوشهر، ایران؛ آگروه مهندسی شیمی دانشگاه خلیج فارس، بوشهر، ایران

چکیده – در این مطالعه، نانوذرات TiO<sub>۲</sub> به منظور دستیابی به بلورینگی بالا و اندازه کوچک ذرات، به روش سل-ژل سینتز شده و سیس مشخصههای نانوذرههای تهیه شده به و سیلهی پراش پرتو ایکس (XRD) و طیف سنج مادون قرمز (FT-IR) ارزیابی شدند. سلول خور شیدی رنگدانههای TiO بر روی زیرلایه شسیشهای FTO راکسید قلع آلاییده شده با استخاده از لایه نشسانی خصیر نانوذرات TiO بر روی زیرلایه شسیشها، از رنگدانه طبیعی (اکسید قلع آلاییده شده با فلوئور) تحت عنوان فیلم اکسید نیمه رسانا ساخته شد. همچنین در این تحقیق، برای کاهش هزینهها، از رنگدانه طبیعی استخراج شده از میوه جمبو استفاده شده است. پارامترهای فتوولتائیک تحت نور خورشید شبیه سازی شده با شدت تابش ۱۰۰ سسان مدار کوتاه، ولتاژ استاندارد (AM۱٫۰۵) اندازه گیری شد. نتایج نشان داد بازده تبدیل انرژی ۱٫۳۶٪ و سایر مشخصه های فتوولتایک شامل جریان مدار کوتاه، ولتاژ مدار باز و فاکتور پر شدن به ترتیب ۴۳۵۰ ۷، ۵٫۸۸ سم/د۳۰٪ و ۷۰٬۳۷۰۶ میباشند.

**کلید و اژه -** رنگدانه طبیعی، روش سل-ژل، سلولهای خورشبدی رنگدانه ای، فتو آند، نانو ذرات TiO<sub>۲</sub>

# Synthesis of TiO<sub>7</sub> nanoparticles using the sol-gel method to fabricate dyesensitized solar cells with natural Syzygium Cumini fruit dye

M. Shadkam', T. Jalali'\*, M. Mehrabi', and S. Osfouri '

Department of Physics, Persian Gulf University, Bushehr, Iran; Department of Chemical Engineering, Persian Gulf University, Bushehr, Iran, \*jalali@pgu.ac.ir

**Abstract** In this study, TiO<sub> $^{\circ}$ </sub> nanoparticles were synthesized using the sol-gel method to obtain a highly crystalline and small particle size of TiO<sub> $^{\circ}$ </sub>; the produced nanoparticles were characterized by X-ray diffraction (XRD) and Fourier transform infrared spectroscopy (FT-IR). Dye-sensitized solar cell (DSSC) was fabricated with a layer of TiO<sub> $^{\circ}$ </sub> nanoparticles paste deposited on FTO (fluorine-doped tin oxide) glass substrate as a semiconductor oxide film. Also in this study, extracted natural dye from Syzygium Cumini fruit was used for decrease the cost. The photovoltaic parameters were measured using the solar simulator under an incident light intensity of  $^{\circ}$  · · · · mW/cm $^{\circ}$  and air mass (AM $^{\circ}$ , o). The results show power conversion efficiency ( $^{\circ}$ ) of  $^{\circ}$ ,  $^{\circ}$  and other photovoltaic parameters include short circuit current density ( $^{\circ}$ ), open-circuit voltage ( $^{\circ}$ ) and fill factor ( $^{\circ}$ FF) are  $^{\circ}$ ,  $^{\wedge}$  MA/cm $^{\circ}$ ,  $^{\circ}$ ,  $^{\circ}$  V and  $^{\circ}$ ,  $^{\circ}$  respectively.

Keywords: Dye-sensitized solar cells, Natural dye; Photoanode, Sol-gel method; TiO<sub>7</sub> nanoparticles

#### 1. Introduction

Dye-sensitized solar cells (DSSCs) have attracted considerable attention due to their low cost and easy fabrication with relatively high photo-conversion efficiency. O'Regan and Grätzel fabricated TiOx based DSSC for the first time in \99\[\]. A typical DSSC is made up of semiconductor oxide film for attaching dye molecules, a counter electrode with deposited layer of platinum and an electrolyte solution. Sun light is absorbed by dye molecules and then electrons are injected to the conduction band of semiconductor oxide. Meanwhile oxidized dye molecules are regenerated by electrolyte solution also electrolyte ions regenerated through counter electrode. Semiconductor oxide film is the heart of DSSCs and the most studied materials are TiO<sub>7</sub>, ZnO and SnO<sub>7</sub> which TiO<sub>7</sub> has announced as the best one due to its unique properties and various advantages such as photochemical stability, high band gap (~7,7 00), 0000 000000 0000000 capability, availability, and non-toxicity. TiO<sub>7</sub> exists in three main phases, namely, rutile, anatase and brookite. However rutile phase is more thermal stable, anatase phase is the first choice for DSSCs applications due to its higher band gap energy [7, nanocrystalline TiO<sub>Y</sub> such as sol-gel, hydrothermal, solvothermal and etc. which sol-gel is one of the most used methods due to highly crystalline and small size of synthesized nanoparticles  $[\xi-1]$ . The sol-gel is a simple, fast, and cost-effective method, which has received much attention due to providing controlled grain size as well as particle morphology, achieving superior purity, compositional homogeneity, low processing temperature, and production with simple equipment. In this work, natural dyes were used to reduce costs and TiO<sub>7</sub> nanoparticles were synthesized using sol-gel method. Then, DSSC was fabricated based on synthesized TiO<sub>7</sub> and photovoltaic performance was evaluated under AM \,o G by measuring currentvoltage curves and calculating  $\eta$ ,  $V_{oc}$ ,  $J_{sc}$ , and FF.

## Y. Experimental

#### 7,1. Materials

The Titanium (IV) isopropoxide (Ti[OCH(CH<sub>r</sub>)<sub>r</sub>]<sub>ε</sub>), ethanol (C<sub>r</sub>H<sub>e</sub>OH), distilled water, nitric acid (HNO<sub>r</sub>), polyethylene glycol (C<sub>r</sub>H<sup>ε</sup><sub>n+</sub>rO<sub>n+</sub>), acetonitrile (C<sub>r</sub>H<sub>r</sub>N), potassium iodide (KIO<sub>r</sub>) and iodine (I<sub>r</sub>), ethylene glycol (C<sub>r</sub>H<sub>r</sub>O<sub>r</sub>), platinum (Pt). Syzygium Cumini fruit and fluorine-doped tin oxide (FTO) conductive glass (sheet resistance  $^{\text{Y}}$   $^{\text{Q}}$ /sq).

#### **Y,Y.** Preparation of TiO<sub>Y</sub> nanoparticles paste

In this method, TiO<sub>7</sub> nanoparticles were synthesized in anatase phase. First, titanium (IV) isopropoxide was added to ethanol under stirring and after few minutes, distilled water was added. Then adding few drops of nitric acid was done to control the pH of prepared solution. To form sol, solution must be stirred vigorously for <sup>r, e</sup> min, then aging for <sup>r, e</sup> hrs to obtain gel. For preparing TiO<sub>7</sub> nanoparticles from gel, it must be dried at <sup>r, e</sup> C then, sintered at <sup>e, e, e</sup> C to get white powder [e]. The procedure of TiO<sub>7</sub> synthesis is shown in Fig. 1. Finally, TiO<sub>7</sub> powder and polyethylene glycol were mixed into the mortar until uniform paste was obtained [<sup>r</sup>].




Fig. 1: The schematic of the synthesis route for TiO<sub>7</sub> via sol-gel method

### Y, T. Preparation of natural dye and electrolyte

It was extracted from fresh Syzygium Cumini fruit and ethanol was used as solvent  $[\land, \land, \cdot]$ . For preparation of electrolyte solution, first,  $\land \cdot$  ml acetonitrile was added to  $\land, \circ$  ml ethylene glycol under stirring. Subsequently,  $\land, \land, \land, \lor \circ$  g potassium iodide and  $\land, \land, \land, \lor \circ$  g iodine was added

The YAth Iranian Conference on Optics and Photonics (ICOP Y·YY)
The YEth Iranian Conference on Photonics Engineering and Technology (ICPET Y·YY)
Shahid Chamran University of Ahvaz, Khuzestan, Iran, Feb. Y-T, Y·YY.

respectively. Prepared electrolyte was stirred until homogenous solution appeared [9].

#### Y.F. Fabrication of DSSC

First, FTO glass substrate ultrasonically cleaned in deionized water, hydrochloric acid, acetone and ethanol respectively and dried at V. °C. Afterwards, the prepared TiO<sub>7</sub> paste was coated on FTO glass, to make photoanode, by doctor blade method and after a few minutes it was heated at 17. °C then, ٤٥٠°C. After cooling, calcinated at photoanode was immersed in dye solution and kept in darkness for YE hrs. For the counter electrode, a thin layer of platinum was deposited on another FTO glass substrate. Finally, photoanode and counter electrode were combined together and sealed using surlyn sheet and electrolyte was injected between them. The active area of the electrode was ., Yo cm'. The photograph of the fabricated DSSC is given in Fig. 7.



Fig. Y: The fabricated DSSC

#### **T.** Results and Discussion

become sharper and the absorbance increases. The FT-IR spectroscopy of the sample were studied which were synthesized via sol-gel method in the range of £··-£···cm<sup>-1</sup> and shown in Fig.£. In this curve, peaks at £Yo cm<sup>-1</sup> and YYY cm<sup>-1</sup> are for O–Ti–O bonding in anatase morphology. The bands centered at Y·£Y cm<sup>-1</sup> and YYAY cm<sup>-1</sup> are the characteristic of surface-adsorbed water and hydroxyl groups. Existing fine peaks also relate to the residual components of organic matter and reactions between water and carbon dioxide, while

the last peak is attributed to the TiO<sub>7</sub>. As well, XRD pattern was done to determine crystal structure of the prepared TiO<sub>7</sub> powder. The XRD peaks in the range of  $\Upsilon\theta$  from  $\Upsilon \cdot ^{\circ} - ^{\circ} \cdot ^{\circ}$ , where the peaks in  $\Upsilon \circ , \xi \upharpoonright \wedge ^{\circ}$ ,  $\Upsilon \lor , \Upsilon \lor \wedge ^{\circ}$ ,  $\Upsilon \land , \Upsilon \xi \sqcap ^{\circ}$ ,  $\xi \land , \Upsilon \Upsilon \urcorner \circ$ ,  $\xi , \Upsilon \xi \not \in ^{\circ}$ ,  $\xi \land , \Upsilon \Upsilon \urcorner \circ$ ,  $\xi , \Upsilon \Upsilon \circlearrowleft \circ$ , and  $\xi , \Upsilon \Upsilon \circlearrowleft \circ$ ,  $\xi , \Upsilon \Upsilon \circlearrowleft \circ$ ,  $\xi , \Upsilon \Upsilon \circlearrowleft \circ$ , and  $\xi , \Upsilon \Upsilon \circlearrowleft \circ$  crystalline structures of anatase. This pattern is represented in Fig.  $\xi , \Upsilon \Upsilon \circlearrowleft \circ$ 




Fig. 7: The UV-visible of the fabricated DSSC




Fig. 4: The FTIR of the fabricated TiOn nanoparticles

The YAth Iranian Conference on Optics and Photonics (ICOP Y·YY)
The YEth Iranian Conference on Photonics Engineering and Technology (ICPET Y·YY)
Shahid Chamran University of Ahvaz, Khuzestan, Iran, Feb. Y-T, Y·YY.

photons absorption. It is expected to enhance the efficiency of dye adsorption by increasing the grain boundaries of the produced TiO<sub>7</sub> using sol-gel method.




Fig. •: Powder XRD pattern of the TiOn nanoparticles




Fig. 7: current density-voltage curve of the fabricated DSSC

### F. Conclusion

TiO<sub>7</sub> nanoparticles have been successfully synthesized using sol-gel method. The synthesized TiO<sub>7</sub> nanoparticles were characterized using XRD, and FTIR techniques. The produced nanoparticles were used as a part of photoanode in the DSSCs. The pastes were prepared with simple method and used in the photoanode of the fabricated DSSCs. The crystallography of the pastes, using X-ray illustrated the existence of TiO<sub>7</sub> in the anatase phase in all samples. The fabricated TiO<sub>7</sub>-based DSSCs demonstrated a light to the electricity conversion

efficiency of ',\".' with a fill factor of "\,o.', open-circuit voltage of ',\" V, and short-circuit current of ",\" mA/cm".

#### References

- [ $\Upsilon$ ] Sharma, A., Karn, R. K., & Pandiyan, S. K. ( $\Upsilon \cdot \Upsilon \cdot \Sigma$ ). Synthesis of TiO $\Upsilon$  nanoparticles by sol-gel method and their characterization. J Basic Appl Eng Res,  $\Upsilon \cdot \Upsilon \cdot \Sigma$ .
- [ $\frac{1}{2}$ ] Vijayalakshmi, R., & Rajendran, V. ( $\frac{1}{1}$ ) Synthesis and characterization of nano-TiO $\frac{1}{2}$  via different methods. Archives of Applied Science Research,  $\frac{1}{2}$ ( $\frac{1}{2}$ ),  $\frac{1}{2}$ .
- [•] Maurya, I. C., Senapati, S., Singh, S., Srivastava, P., Maiti, P., & Bahadur, L. ('`\^\). Effect of Particle Size on the Performance of TiO\' Based Dye-Sensitized Solar Cells. ChemistrySelect, \(^(\mathbb{r}\_{\xi})\), \(^{\alpha\nu\gamma}\cdot\).
- [7] Jeng, M. J., Wung, Y. L., Chang, L. B., & Chow, L. (7.17). Particle size effects of TiO7 layers on the solar efficiency of dye-sensitized solar cells. International Journal of Photoenergy, 7.17.
- [^] Golshan, M., Osfouri, S., Azin, R., & Jalali, T. (^, ^, ). Fabrication of optimized eco-friendly dyesensitized solar cells by extracting pigments from low-cost native wild plants. Journal of Photochemistry and Photobiology A: Chemistry, ^^^, 117191.
- [¶] Gu, P., Yang, D., Zhu, X., Sun, H., Wangyang, P., Li, J., & Tian, H. (¬¬¬). Influence of electrolyte proportion on the performance of dye-sensitized solar cells. AIP Advances, ¬(¬¬¬), ¬¬¬¬¬¬¬.

The YAth Iranian Conference on Optics and Photonics (ICOP Y·YY)
The YEth Iranian Conference on Photonics Engineering and Technology (ICPET Y·YY)
Shahid Chamran University of Ahvaz, Khuzestan, Iran, Feb. Y-T, Y·YY.

[1.] Hambali, N. A. M. A., Yusof, N. R., Norhafiz Hashim, M., & Mat Isa, S. S. (1.10). Dye-Sensitized Solar Cell Using Syzygium Cumini Fruit as Natural Dye Utilizing Titanium Dioxide. In Applied Mechanics and Materials 102-100, 1117.